






Pin数	尺寸A	尺寸B
1		5.08
2	5.08	10.16
3	10.16	15.24
4	15.24	20.32
5	20.32	25.40
6	25.40	30.48
7	30.48	35.56
8	35.56	40.64
9	40.64	45.72
10	45.72	50.80
11	50.80	55.88
12	55.88	60.96
13	60.96	66.04
14	66.04	71.12
15	71.12	76.20
16	76.20	81.28
17	81.28	86.36
18	86.36	91.44
19	91.44	96.52
20	96.52	101.6



塑胶为白色



PCB LAYOUT



技术规范：
额定电流：7AMP
适用温度：-40℃to+105℃
接触电阻：20mΩ Max
绝缘电阻：1000MΩ Min
耐电压：AC 500V
绝缘材料：Polyester (UL94V-0)
Standard:LCP+GF30
端子材质：Brass
电镀规范：Au or Sn Over 50u” Ni

P a-10-1-2-5p-a-a-s-0									
排针系列	间距	塑高	双塑	单排	PIN位	电镀	材质	角度	备注
	a=0.8mm	1.0-10	1-单塑	1-单排	1*40P/50P	A=1u”	A-PBT	S=180°	0-3.0
	b=1.0mm	1.5-15	2-双塑	2-双排	2*40/50P	B=3u”	B-PA46	R=90°	1-3.0/6.0(双塑)
	c=1.27mm	2.0-20	3-三塑	3-三排	3*40/50P	C=5u”	C-PA6T	M=SMT	2-3.0/3.0(双塑)
	d=2.0mm	2.54-254		4-四排	4*40/50P	D=10u”	D-PA9T	Z=Z型	3-2.8/4.0(双塑)
	e=2.5mm	4.3-43				E=15u”	E-LCP	Y=135°	4-2.6/3.5(双塑)
	f=2.54mm	7.4-74				F=30u”		L=卧式SMT	其它另做说明
	g=3.96mm					S=镀锡			
	h=5.08mm					H=半金锡			

TOLERANCE:
X. ±XXX
.X ±0.20
.XX ±0.10
ANG.

STO

上海狮拓电子科技有限公司

產品名稱:
產品料號:

THIRD ANGLE PROJECTION

簽名
日期
審核
日期

客戶確認
☐ 承認
☐ 駁回

5.08mm单排针，180°，塑高3.2mm
Spec:5.08mm Board Spacer, Single Row, Straight
Positions: 1×1×1×20
Plastic Height: 3.2mm