






技术规范:

额定电流 : 3AMP
适用温度 : -40°C to +105°C
接触电阻 : 20mΩ Max
绝缘电阻 : 1000MΩ Min
耐电压 : AC 1000V
绝缘材料 : Polyester (UL94V-0)
Standard: PA-6T
端子材质 : Bronze
电镀规范 : Au or Sn Over 50u" Ni

Pin#	尺寸A	尺寸B
2x2	2.54	5.48
2x3	5.08	8.02
2x4	7.62	10.56
2x5	10.16	13.10
2x6	12.70	15.64
2x7	15.24	18.18
2x8	17.78	20.72
2x9	20.32	23.26
2x10	22.86	25.80
2x11	25.40	28.34
2x12	27.94	30.88
2x13	30.48	33.42
2x14	33.02	35.96
2x15	35.56	38.50
2x16	38.10	41.04
2x17	40.64	43.58
2x18	43.18	46.12
2x19	45.72	48.66
2x20	48.26	51.20
2x21	50.80	53.74
2x22	53.34	56.28
2x23	55.88	58.82
2x24	58.42	61.36
2x25	60.96	63.90
2x26	63.50	66.44
2x27	66.04	68.98
2x28	68.58	71.52
2x29	71.12	74.06
2x30	73.66	76.60
2x31	76.20	79.14
2x32	78.74	81.68
2x33	81.28	84.22
2x34	83.82	86.76
2x35	86.36	89.30
2x36	88.90	91.84
2x37	91.44	94.38
2x38	93.98	96.92
2x39	96.52	99.46
2x40	99.06	102.00



F a-10-1-2-5p-a-a-s-D-0									
引脚系列	间距	插孔	双排	单排	Pin数	长度	材质	角度	端子
a-0.0mm			1-单排	1-单排	1"40P/50P	B-10"	A-70T	S-180°	12.5mm间距25
b-1.0mm			2-双排	2-双排	2"40P/50P	B-30"	B-70T/60	R-90°	11.0mm间距18
c-1.27mm			3-三排	3-三排	3"40P/50P	C-50"	C-70T/60	R-90°	12.5mm间距18
d-2.0mm			4-四排	4-四排	4"40P/50P	D-100"	D-70T/60	L-90°	12.5mm间距18
e-2.5mm						B-150"	B-70T/60	L-135°	100-非焊接端子
f-3.0mm						B-200"	B-70T/60	S-90°	100-非焊接端子
h-5.08mm						B-250"	B-70T/60	S-90°	100-非焊接端子
									其它另做说明
									注: 本规格以原厂计

TOLERANCE:		客户确认	
X. ±XXX		日期	日期
X. ±0.20		审核	日期
XX ±0.10		□ 返回	日期
ANG.			
STO		上海狮拓电子科技有限公司	
产品名称:		THIRD ANGLE PROJECTION	
产品料号:			