






技术规范:

额定电流 : 1AMP
适用温度 : -40℃to+105℃
接触电阻 : 20mΩ Max
绝缘电阻 : 1000MΩ Min
耐电压 : AC500V
绝缘材料 : Polyester (UL94V-0)
Standard: PA-6T
端子材质 : Brass
电镀规范 : Au or Sn Over 50u" Ni

Pin脚	尺寸A	尺寸B	尺寸C
2x5	5.08	9.55	8.89
2x6	6.35	10.82	10.16
2x7	7.62	12.09	11.43
2x8	8.89	13.36	12.70
2x9	10.16	14.63	13.97
2x10	11.43	15.90	15.24
2x11	12.70	17.17	16.51
2x12	13.97	18.44	17.78
2x13	15.24	19.71	19.05
2x14	16.51	20.98	20.32
2x15	17.78	22.25	21.59
2x16	19.05	23.52	22.86
2x17	20.32	24.79	24.13
2x18	21.59	26.06	25.40
2x19	22.86	27.33	26.67
2x20	24.13	28.60	27.94
2x21	25.40	29.87	29.21
2x22	26.67	31.14	30.48
2x23	27.94	32.41	31.75
2x24	29.21	33.68	33.02
2x25	30.48	34.95	34.29
2x26	31.75	36.22	35.56
2x27	33.02	37.49	36.83
2x28	34.29	38.76	38.10
2x29	35.56	40.03	39.37
2x30	36.83	41.30	40.64
2x31	38.10	42.57	41.91
2x32	39.37	43.84	43.18
2x33	40.64	45.11	44.45
2x34	41.91	46.38	45.72
2x35	43.18	47.65	46.99
2x36	44.45	48.92	48.26
2x37	45.72	50.19	49.53
2x38	46.99	51.46	50.80
2x39	48.26	52.73	52.07
2x40	49.53	54.00	53.34
2x41	50.80	55.27	54.61
2x42	52.07	56.54	55.88
2x43	53.34	57.81	57.15
2x44	54.61	59.08	58.42
2x45	55.88	60.35	59.69
2x46	57.15	61.62	60.96
2x47	58.42	62.89	62.23
2x48	59.69	64.16	63.50
2x49	60.96	65.43	64.77
2x50	62.23	66.70	66.04

F a-10-1-2-5p-a-a-s-D-0									
排针系列	间距	插高	双排	单排	Pin数	电镀	材质	角度	端子
a-0.5mm			1-单排	1-单排	1"40P/50P	A-1u"	A-70P	S-180°	12.5mm间距25
b-1.0mm			2-双排	2-双排	2"40P/50P	B-5u"	B-70P/60P	R-90°	11.0mm间距18
c-1.27mm			3-三排	3-三排	3"40P/50P	C-5u"	C-70P/60P	R-90°	12.2mm间距22
d-2.0mm			4-四排	4-四排	4"40P/50P	D-10u"	D-70P/60P	L-45°	100#非标准端子
e-2.5mm						E-15u"	E-12P	L-135°	4-2.0/2.5(双排)
f-3.0mm						F-30u"			100#非标准端子
h-5.08mm						H-50u"			100#非标准端子
						R-半全插			其它另做说明
									注: 本插针以原设计

TOLERANCE:

X. ±XXX

XX ±0.20

ANG. ±0.10

ST

上海狮拓电子科技有限公司

產品名稱:

產品料號:

THIRD ANGLE PROJECTION

簽名

日期

審核

日期

客戶確認

☐承認

☐撤回

日期

日期

1.27间距筒牛, SMT, 壁高5.7mm

Spec: 1.27mm Box Header , SMT

Positions: 10~100

Plastic Height: 5.7mm