




Technical Data

Material:

Pin(outer sleeve):Brass,machined
CuZn38Pb2

Plating(outer sleeve):


Tin Plated:2μm/80μm"NI, 5μm/200μ"Sn

Gold Plated:2μm"/80μm"Ni, 0.8μ" gold

Plating(Contact):2μm/80μ"NI, gold or
Tin plated

Insuiator:PPS UL94V-0

ClIp(Contact 4 Flnger):Beryllium
copper,heat teated



Electrical:

Current rating:3Amps/contact max.

Contact resistance:≤4mΩ/contact

Insuiation resistance:≥1000MΩ at
V=100V

Operaing voitage:60VAC/DC

Mechanical:

Average Insertion force with steel pin
of ø0.432:<250g

Average withdrawal force with steel pin
of ø0.432:>70g

Mechanical lige cycle:min 200

Operaling temperature:-40° C to+105° C

Soldering temperature:+255° C

TOLERANCE:

X. ±XXX

.X ±0.20

.XX ±0.10

ANG.



上海狮拓电子科技有限公司

產品名稱:

產品料號:

THIRD ANGLE PROJECTION



簽名 _____

日期 _____

審核 _____

日期 _____

客戶確認

☐ 承認 _____ 日期 _____

☐ 駁回 _____ 日期 _____