

A

B

C



D

E

1

2

3



Technical Data

Material:

Pin(outer sleeve):Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated: $2\mu\text{m}/80\mu\text{m}$ NI, $5\mu\text{m}/200\mu\text{m}$ Sn

Gold Plated: $2\mu\text{m}/80\mu\text{m}$ Ni, $0.8\mu\text{m}$ gold

Plating(Contact): $2\mu\text{m}/80\mu\text{m}$ NI, gold or Tin plated

Insulator:PPS UL94V-0

ClIp(Contact 4 Flnger):Beryllium copper,heat teated

Electrical:

Current rating:3Amps/contact max.

Contact resistance: $\leq 4\text{m}\Omega$ /contact

Insuiation resistance: $\geq 1000\text{M}\Omega$ at $V=100\text{V}$

Operaing vottage:60VAC/DC

Mechanical:

Average Insertion force with steel pin of $\phi 0.432$: $<250\text{g}$

Average withdrawal force with steel pin of $\phi 0.432$: $>70\text{g}$

Mechanical lige cycle:min 200

Operaling temperature: -40°C to $+105^\circ\text{C}$

Soldering temperature: $+255^\circ\text{C}$

TOLERANCE:

X. ± 0.05

.X ± 0.20

.XX ± 0.10

ANG.



產品名稱:

產品料號:

上海狮拓电子科技有限公司

THIRD ANGLE PROJECTION



簽名 _____

日期 _____

審核 _____

日期 _____

客戶確認

☐ 承認 _____ 日期 _____

☐ 駁回 _____ 日期 _____

STOA-P168XXXX0740B