


Technical Data

Material:

Pin(outer sleeve):Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated:2 μ m/80 μ m"NI, 5 μ m/200 μ m"Sn

Gold Plated:2 μ m"/80 μ m"Ni, 0.8 μ " gold

Plating(Contact):2 μ m/80 μ m"NI,gold or Tin plated

Insulator:PPS UL94V-0

Clip(Contact 4 Flnger):Beryllium copper,heat teated

Electrical:

Current rating:3Amps/contact max.

Contact resistance: $\leq 4m\Omega$ /contact

Insulation resistance: $\geq 1000M\Omega$ at V=100V

Operaing voitage:60VAC/DC

Mechanical:

Average Insertion force with steel pin of $\varnothing 0.432$:<250g

Average withdrawal force with steel pin of $\varnothing 0.432$:>70g

Mechanical life cycle:min 200

Operaling temperature:-40 ° C to+105 ° C

Soldering temperature:+255 ° C

TOLERANCE:

X. $\pm XXX$

.X ± 0.20

.XX ± 0.10

ANG.



產品名稱:

產品料號:

上海狮拓电子科技有限公司

THIRD ANGLE PROJECTION



簽名 _____

日期 _____

審核 _____

日期 _____

客戶確認

☐ 承認 _____ 日期 _____

☐ 駁回 _____ 日期 _____

ST0A-P133XXXX0740B